

US010424318B2

(12) United States Patent

Levy-Rosenthal

(10) Patent No.: US 10,424,318 B2

(45) **Date of Patent:** Sep. 24, 2019

(54) METHOD, SYSTEM AND PROGRAM PRODUCT FOR PERCEIVING AND COMPUTING EMOTIONS

(71) Applicant: Patrick Levy-Rosenthal, New York,

NY (US)

(72) Inventor: Patrick Levy-Rosenthal, New York,

NY (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 603 days.

(21) Appl. No.: 14/254,276

(22) Filed: Apr. 16, 2014

(65) Prior Publication Data

US 2015/0012463 A1 Jan. 8, 2015

Related U.S. Application Data

- (60) Provisional application No. 61/812,260, filed on Jul. 5, 2013.
- (51) Int. Cl. G06N 5/04 (2006.01) G10L 25/63 (2013.01) G10L 25/90 (2013.01)
- (58) Field of Classification Search

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

8,996,429 B1 3/2015 Francis, Jr. et al. 2006/0167694 A1 7/2006 Mitsuyoshi

OTHER PUBLICATIONS

Rabie, Audio-Visual Emotion Recognition for Natural Human-Robot Interaction, Doctoral Thesis, University of Bielefeld, 2010, pp. 1-118 (Year: 2010).*

Breazeal (Ferrell), Cynthia, "Early Experiments using Motivations to Regulate Human-Robot Interaction," AAAI Fall Symposium on Emotional and Intelligent: The tangled knot of cognition, Technical Report FS-98-03, Mar. 1998 (6 pages).

"Emotion Engine," archived Wikipedia article, last edited Apr. 28, 2013, retrieved from https://en.wikipedia.org/wiki/Emotion_Engine (5 pages).

* cited by examiner

Primary Examiner — Wilbert L Starks (74) Attorney, Agent, or Firm — McCarter & English, LLP

(57) ABSTRACT

A method, system and program product comprise monitoring inputs, into a system, for detected actions from a user. At least one detected action is identified. At least a first database storage location associated with the user is accessed. The first database storage location is at least configured for storage of emotional profiles of the user. At least a second storage location associated with the system is accessed. The second storage location is at least configured for storage of emotional profiles of the system. The at least one detected action is processed in a computational machine using data from the first storage location to determine a status of the user. A response to the status of the user is calculated. The response is at least in part determined by the status of the user and data contained in the second storage location.

24 Claims, 10 Drawing Sheets

